

ACTOR 325 & 625



ACTOR 325



ACTOR 625



ACTOR 325 with RCD



ACTOR 625 with RCD



ACTOR 325 with MCBs P+N



ACTOR 625 with MCBs P+N



ACTOR 325 with RCD & MCBs P+N



ACTOR 625 with RCD & MCBs P+N

REAR SIDES



Rear side of ACTOR 325



Rear side of ACTOR 625



Power inlet CEE 5X32A (for ACTOR 325) or CEE 5X63A (for ACTOR 625) are supplied with every Dimmer Pack.

TECHNICAL SPECIFICATIONS	ACTOR MODELS		
	616	325	625
NUMBER OF CHANNELS	6	3	6
CHANNEL CAPACITY (WATTS at 230V)	3680W	5750W	5750W
MAXIMUM CURRENT PER CHANNEL	16A	25A	25A
DMX-512 SIGNAL BUFFER	YES	YES	YES
THREE LAWS (LINEAR-INCANDESCENT-SWITCH) SELECTABLE PER CHANNEL	YES	YES	YES
SUPPLY VOLTAGE 400/230V~3/N/PE/50HZ	YES	YES	YES
DIMENSIONS IN MM (WxDxH):	ACTOR 325 & ACTOR 616 (EXCEPT ACTOR 616 WITH SCREW TERMINALS)		482x132x340
	ACTOR 625		482x177x340
	ACTOR 616ST (WITH SCREW TERMINALS)		482x132x375